

Anomaly Trends for Missions to Mars: Mars Global Surveyor and Mars Odyssey

Nelson W. Green and Alan R. Hoffman,

Jet Propulsion Laboratory, Pasadena, CA USA California Institute of Technology

Presented at the

46th AIAA Aerospace Sciences Meeting and Exhibit Grand Sierra Resort, Reno, Nevada

January 10th, 2008



Topics



- Objectives
- Anomalies by Time
 - Mars Global Surveyor
 - Mars Odyssey
- Anomalies by Type
 - Anomaly Sources
 - Corrective Actions
- Conclusions







Objectives


- Conducted as a part of NASA Ultra-Reliability effort
 - Goal is to design for increased reliability in all NASA missions
 - Desire is to increase reliability by a factor of 10
 - Study provides a baseline for current technology
- Analyzed anomalies for spacecraft orbiting Mars
 - Long lived spacecraft
 - Comparison with current rover missions and past orbiters
- Looked for trends to assist design of future missions
 - How many anomalies?
 - When did they occur?
 - Where did they coming from?
 - What kinds of responses?




Mars Global Surveyor

- Launched 7 November 1996
- Mars Orbit Insertion 11 September 1997
- Second use of Aerobraking to get to final science orbit
 - Sept 1997 to Oct 1997
 - Nov 1997 to May 1998
 - Sept 1998 to Feb 1999
- Mapping of surface began in April 1999
- Primary mission completed in January 2001
- Extended mission through November 2006 when the spacecraft was lost










Mars Global Surveyor

- MGS was a return to Mars after loss of Mars Observer in 1992
 - Six primary instruments
 - Several came from MO project
- Spacecraft constructed and operated by Lockheed Martin
 - Oversight for NASA provided by JPL
- An example of a very successful mission long life mission
 - Ten years of operation











Mars Odyssey

- Launched on 7 April 2001
- Mars Orbit Insertion on 24 October 2001
- Aerobraking utilized to achieve final science orbit
 - Completed in January 2002
- Primary mission February 2002 to August 2004
- Extended mission begun in August 2004










Mars Odyssey





- Spacecraft built and operated by Lockheed Martin
 - Oversight for NASA by JPL
- Three primary science instruments
 - Several secondary instruments
- Return to Mars after loss of MCO and MPL
- Serves as primary relay for Mars Exploration Rovers



In-flight Anomaly Reporting

- Incident Surprise Anomaly (ISA) Reports
- Document anomalies on spacecraft or ground support system during operations
 - Process
 - Problem described
 - Verification
 - Corrective Action Taken
 - Review and Approval
 - Closure
- 1160 Mars Global Surveyor ISAs evaluated
- 536 Mars Odyssey ISA evaluated




Anomalies by Time

- Anomalies were plotted as a function of time
 - Units were number of anomalies per month
 - All anomalies counted
 - No preference given for criticality
 - Ground and Flight based anomalies grouped together
- Key trends from plots
 - Months with the most anomalies at beginning of mission
 - Key milestones often have peaks in anomaly reporting
 - Decreasing numbers of anomaly reports with increasing mission time






Anomalies by Time - MGS







Anomalies by Time - Odyssey






Anomalies by Time

- Trends identified can be see for both missions
- MGS
 - Peak early in mission is less prominent
 - Localized peaks not as closely tied to spacecraft activity
 - May be due to ground bases issues
 - Large low region during Faster, Better, Cheaper paradigm
- Odyssey
 - Majority of anomalies occurred early in mission
 - Peaks with mission activity
- Overall decrease in anomaly reports with time
- Compares well with other missions previously examined
 - Next few slides show examples




Anomalies by Time – MER






Anomalies by Time – Voyager and Galileo

Voyager - ISA Quantities by Year



Galileo -Quantities by Year





Anomalies by Time

- Trends seen on MGS and Odyssey are typical
 - Large numbers of anomalies at beginning
 - Mission team learning to operate spacecraft
 - New ground control equipment
 - New software to work out
 - Peaks at periods of high activity
 - More emphasis given to spacecraft at that time
 - Systems reactivated if dormant
 - Increased activity = More anomalies seen
 - Number of anomaly reports decreases with increasing mission time
 - More familiarity with spacecraft and ground systems
 - Many bugs have been worked out
 - Smaller mission teams



Anomalies by Type

- Database of ISA reports created for both MGS and Odyssey
 - MGS: 1160 ISAs
 - Odyssey: 536 ISAs
- Each anomaly individually reviewed and characterized
- The description of event was used to determine the source of the anomaly
 - Five generalized anomaly sources identified
 - Followed pattern of previous parts of this study
- Examined real-time and overall corrective actions to determine mission team response

16

- Five generalized corrective actions used
- Incomplete (open) reports labeled "Unknown"




- Flight Hardware
 - Spacecraft component anomaly or failure
- Ground Hardware
 - Mission Control or Deep Space Network facilities
- Flight Software
 - Software event on board spacecraft
- Ground Software
 - Software event on Earth based computers
- Procedure
 - Improper procedure
 - Lack of prior knowledge







Anomalies Sources - MGS









Anomalies Sources - Odyssey





Anomalies Sources





Mars Global Surveyor 1996 – 2006 : 1160 ISAs Mars Odyssey 2001 – April 2007 : 536 ISAs




- Ground based anomalies represent ²/₃ to ³/₄ of all anomalies for both missions
- Ground Software anomalies are most prevalent
 - Control sequence generation issues
 - Data processing / storage issues
 - Ground support software
 - Login errors
- Ground Hardware anomalies were less dominate
 - More common on MGS
 - Issues with DSN hardware
 - Lockheed to JPL connection issues
- Procedure issues least common



- Flight based anomalies represent ¼ to ⅓ of all anomalies
- Fairly equal balance for both missions
 - Flight Hardware
 - MGS:11%
 - Odyssey: 16%
 - Flight Software
 - MGS: 13%
 - Odyssey: 21%
- These results are similar to other recent missions analyzed, but differ from earlier missions








- "Use As Is"
 - Essentially taking no action
- Flight software
 - Base software and uploaded commands
 - Fix hardware and software issues on board spacecraft
- Ground software
 - Earth based computers
- Ground Hardware
 - Changing Earth based hardware
 - Mission Control
 - Deep Space Network
- Procedure
 - Spacecraft operations
- ___Mission team operations







Corrective Actions - MGS









Corrective Actions - Odyssey









Mars Global Surveyor 1996 – 2006 : 1160 ISAs Mars Odyssey 2001 – April 2007 : 536 ISAs




- Ground Software corrective actions are most common response
 - Not surprising based on anomaly sources charts
 - Not a one-to-one match
- "Use As Is" next most common
 - Essentially to take no action
 - Used when nothing could or should be done
- Procedure corrective action
 - Much more common as a corrective action than as the source of an anomaly
 - Changes in how the mission teams work
 - Changes in approach to utilizing spacecraft



- Flight Software corrective action
 - Not the dominate response with either mission
 - Used for flight software issues
 - Sometimes used for flight hardware issues
- Ground Hardware
 - Generally least common response
 - Much more common on MGS than other missions
 - Issues with communication systems
 - Issues with computers



Corrective Actions – Four missions studied






Anomaly Sources and Corrective Actions

- Corrective actions generally linked to anomaly sources
 - Response is usually the of the same type as anomaly
 - Not a one-to-one relationship
- Not possible with Flight Hardware anomalies
 - Getting technician to spacecraft is slightly difficult when in flight
 - Most common responses
 - "Use As Is"
 - Flight Software modification
 - Includes modified operational sequences

Procedure change



Anomaly Sources and Corrective Actions



2001 - April 2007 : 536 ISAs



Conclusion

- Greatest number of anomalies occur early in mission
 - Steep learning curve for mission teams
 - Working out kinks in spacecraft and systems
- Peaks in anomalies with periods of high activity
 - More attention given to mission
 - Anomalies may have greater impact on mission
- Numbers of anomalies decrease with increasing mission time
 - Fewer people on mission team
 - More familiarity with spacecraft and systems
 - Fewer instruments in operation (due to other failures?)



Conclusion

- Ground software anomalies most common
 - For missions within the last decade
 - Increased complexity and reliance on computer based systems
 - Other types of anomalies fairly equally distributed
- Most anomalies from ground based systems
 - 65% to 75%
 - Ground Software + Ground Hardware + Procedure
- Corrective actions generally of same type as anomaly source
 - Not always but as a general statement
 - Flight Hardware is the exception



Acknowledgements

The research described in this paper was carried out at the Jet Propulsion Laboratory, the California Institute of Technology under a contract with the National Aeronautics and Space Administration. The authors gratefully acknowledge the following colleagues for their contributions of data and expertise: A. Shapiro, A. Nikora, H. Kirkham, and P. Bowerman.



Backup Slides



Anomaly Sources vs. Corrective actions Mars Global Surveyor

Corrective Actions

Mission: Mars Global Surveyor	Use As Is None	FS - Flight Software	GH - Ground Hardware	GS - Ground Software	Procedure	Unknown	totals
FH - Flight Hardware	49	52	0	2	22	0	125
FS - Flight Software	39	66	0	12	35	0	152
GH - Ground Hardware	30	0	110	41	16	3	200
GS - Ground Software	110	0	42	355	68	8	583
Procedure	16	3	0	1	80	0	100
totals	244	121	152	411	221	11	1160

nomaly Sources



Anomaly Sources vs. Corrective actions Mars Odyssey

Corrective Actions

Mission: Odyssey	Use As Is None	FS - Flight Software	GH - Ground Hardware	GS - Ground Software	Procedure	Unknown	totals
FH - Flight Hardware	42	30	0	1	13	1	87
FS - Flight Software	20	67	0	4	17	5	113
GH - Ground Hardware	12	0	22	16	8	2	60
GS - Ground Software	24	0	1	181	32	3	241
Procedure	3	0	0	1	31	0	35
totals	101	97	23	203	101	11	536

ynomaly Sources



Anomaly Sources vs. Corrective actions Mars Exploration Rovers – Surface Ops

Corrective Actions

Mission: MER surface totals	Use As Is None	FS - Flight Software	GH - Ground Hardware	GS - Ground Software	Procedure	Unknown	totals
FH - Flight Hardware	48	20	0	4	45	6	123
FS - Flight Software	39	42	0	9	25	6	121
GH - Ground Hardware	2	0	21	3	1	1	28
GS - Ground Software	37	0	2	114	14	14	181
Procedure	5	0	0	4	40	4	53
totals	131	62	23	134	125	31	506

Anomaly Sources



Anomaly Sources vs. Corrective actions Galileo

Corrective Actions

Mission: Galileo	Use As Is None	FS - Flight Software	GH - Ground Hardware	GS - Ground Software	Procedure	Unknown	totals
FH - Flight Hardware	187	92	11	12	58	10	370
FS - Flight Software	88	71	0	53	55	9	276
GH - Ground Hardware	13	1	33	0	11	0	58
GS - Ground Software	10	4	1	48	30	2	95
Procedure	10	3	1	2	77	5	98
totals	308	171	46	115	231	26	897

Anomaly Source